



KFK-7090D Rollfed Flatbed Cutter



AUTO FEEDING DIGITAL FLATBED CUTTER

High-quality felt, Dual blade structure, HD Touch Screen

- Servo motor, imported guide rail, intelligent Al calculation, fast and accurate cutting
- Camera real-time tracking, easy handling of complex patterns, precise and stable contour cutting
- HD LCD touch screen, clear interface, easy operation
- Easily switch between half-cut and full-cut modes
- Multi-zone vacuum adsorption, low noise and strong suction, adaptable to various graphic cutting











Specifications Model KFK-7090D **Cutting Speed** 1mm/s-800mm/s **Cutting Thickness** ≤1.2mm **Cutting Accuracy** 0.05mm 105cm Cutting Pressure (KG) 1kg Cutting area 60cm*80cm| ≤23.62"*31.5"inch Packaging printing, 146cm 130cm **Application Scenarios** paper products industry, garment cutting, label industry, automotive industry **Cutting Materials** UV DTF film, DTF film, etc. Half-cut, full-cut **Cutting Mode** Positioning Method Camera positionina Operation Interface HD touch screen, multi-language support Material Holding Method Vacuum adsorption Working Method Roll-type felt automatic feeding **Drive Method** High-speed servo drive Standard Interfaces USB, USB flash drive offline, Ethernet port PrintFactory Production/SignMaster/Ai/AutoCAD/CDR Compatible Software Compatible Format: HPGL Windows7/Windows10/Windows11 Computer System Blade Head Dual blade structure 110V/220V, 50~60HZ, Power Supply/Power Power: Machine 2.5kw, Air pump 1.5kw Machine: 146cm×130cm×105cm | 57.48"×51.18"×41.34" Air pump: 39cm*37cm*35cm | 15.35"×14.56"×13.78" Size Package: 170cm×128cm×120cm | 66.93"×50.39"×47.24" N.W: Machine: 220kg | 485lb, Air pump: 20kg | 44.1lb weight G.W: 360kg | 793.66lb 50%-60% Humidity 18°C-28°C | 64.4°F-82.4°F **Temperature**

Contact information

https://axprinter.com
Tél: +33 (0) 6 26 65 58 20
E-mail: info@axprinter.com

