

Easymount Hybrid, bringing something new to the table.

KEY FEATURES

- Patented roll fed-applicator combination
- Patented unique hover technology.
- Swing-out arms for easier loading of laminate and film.
- Pneumatic air pressure
- 6m/20ft a minute
- 45mm/1.8" mounting thickness
- Variable speed control
- Foot pedal
- Reverse mode
- Multilingual control panel



BRITISH DESIGN



GREAT FOR USE IN

- Sign makers
- Print finishers

IDEAL WHEN LAMINATING

- Single banners
- Reel-to-reel laminates
- Posters, graphics and signs
- Mounting prints to boards
- Pop-up displays
- Applying vinyls, tapes and adhesive films
- Outdoor signage
- and many more...

BRAND NEW multi-patented Easymount Hybrid laminator, with unique HOVER technology. Incorporating both a traditional roll-fed laminator and flatbed applicator. Giving benefits of both of these applications in one system.

- *World's first laminator and applicator, all in one.*
- *Roll to Roll technology for long run, roll-fed laminating.*
- *Patented floating rollers, save time, and keep's boards in perfect condition.*
- *Modular design, Length from 1.5 meters to unlimited lengths. Configured to grow with your business.*

Specifications	Easymount Hybrid
Laminating Speed (m/ft/min)	6m/20ft
Max. Width (mm/inches)	1600mm/63"
Mounting Thickness (mm/inches)	45mm/1.8"
Roller Diameter (mm/inches)	130mm/5"
Laminating Temperature (°C/°F)	0-60°C/32-140°F
Pressure Adjustment	Pneumatic (Optional silent compressor or use an existing air supply)
Film Core (mm/inches)	77mm/3"
Power Supply AC (V-Hz)	220/240-50-60
Power Consumption (W)	1500
Overall Dimensions (mm/inches)	2200x2900x1500mm/87x114x59"(Main Unit) 1530x2900x1500mm/87x114x60"(Modular Unit)
Gross Machine Weight	680kg(Main unit) / 520kg (Modular Unit)
Warranty*	1 year

*For full terms & conditions of warranty, please visit www.vividonline.com/support/warranty_information

